

## Flow Sensors – BSP

### Flow Sensing for Maxicom<sup>2</sup>, SiteControl<sup>™</sup>, IQ<sup>™</sup> v2.0, LXD, LXME, LXMEF

Rain Bird flow sensors send flow data to central control or stand-alone control systems for precise and accurate flow monitoring. Rain Bird flow sensors enable you to capitalize on the advantages of Flow Management functionality. Use Rain Bird Flow Sensors with Rain Bird Maxicom<sup>2</sup>, SiteControl and IQ v2.0 central control applications or in standalone systems using Rain Bird LXD, LXME and LXMEF controllers to benefit from:

**Flo-Watch<sup>™</sup>.** Flo-Watch constantly monitors for low flow and excess flow conditions caused by broken lines or heads, automatically quarantines and shuts down the problem area and continues to irrigate non affected areas. Saves water, saves plant material and enables irrigation programs to continue and complete.

**Learned Flow.** The controller automatically learns station flow rates resulting in more accurate flow rates. The automatic collection prevents you from having to manually enter data from drawings or physically visiting each valve to collect flow data and manually entering the data into a controller.

**FloManager<sup>®</sup>.** FloManager determines the optimal station irrigating sequence. The system runs at its fullest capacity until programs are complete. The controller automatically selects and runs multiple valves at the same time within hydraulic parameters allowing for shorter water windows. Pressure and flow rates may be manually measured and entered into the controller to utilize FloManager functionality. Using a flow sensor and learned flow capabilities can help to optimize system performance.

Customers with ESP-LXME units only need to purchase a Flow Smart Module for the ESP-LXME to capitalize on Flo-Watch, Learned Flow and FloManager. Add IQ v2.0 to remotely manage your ESP-LXD, ESP-LXMEF and ESP-LXME controllers. Centrally managing your controllers with IQ v2.0 saves labor and time by eliminating constant monitoring of the site and trips to the controllers. Retrieve alarms or receive alarms via email regarding problem areas to dispatch maintenance personnel to check and repair.

### Configuration

#### Maxicom<sup>2</sup> and SiteControl - (Hard Wire)

**Two-Wire Satellite Systems:** The Flow Sensor is installed with a Pulse Transmitter and a Rain Bird Pulse Decoder (DECPULLR).

**Maxicom<sup>2</sup> - Link Radio Satellite Systems:** The Flow Sensor is installed with a Pulse Transmitter (no decoder required).

**SiteControl - Decoder System:** Software version 2.X or lower, the flow sensor is installed with a Pulse Transmitter and a Two-Wire Decoder Sensor Decoder (SD211TURF). Software version 3.X or higher, the flow sensor is installed with a Two-Wire Decoder Sensor Decoder (pulse transmitter is optional).

**IQ v2.0 - (Hard Wire) Two-Wire Systems:** The Flow Sensor is installed with a Two-Wire Decoder Sensor Decoder (SD211TURF) (no pulse transmitter required).

**IQ2 v2.0 - Traditional Wired Systems:** Only the flow sensor is installed (no pulse transmitter, no decoder required).

**LXD - (Hard Wire) Two-Wire Systems:** The Flow Sensor is installed with a Two-Wire Decoder Sensor Decoder (SD211TURF) (no pulse transmitter required).

**LXMEF - Traditional Wired Systems:** Only the flow sensor is installed (no pulse transmitter, no decoder required).

Surge protection (FSSURGEKIT) is recommended for all systems - One at the Flow Sensor, and if more than 50' of wire run, one at the Pulse Transmitter.

### Features (Sensors)

- Simple six-bladed impeller design
- Designed for outdoor or underground applications
- Available in PVC, brass or stainless steel construction
- Pre-installed in tee or insert versions

### Features (Transmitters)

- Reliable solid-state design
- Display or signal-alone versions
- Easy-to-program, menu-driven design
- Programmable from a laptop computer (PT322)
- Operates with both MAXILink<sup>™</sup> and (hard wire) two-wire satellite systems
- Mounted in optional NEMA enclosure (PT3002 only)



### How To Specify

#### IFS - 100 - P - BSP

IFS =  
International  
Flow Sensor

BSP = Female BSP  
FL = Din Flanged

B = Brass  
P = Plastic (PVC)  
SS = Stainless Steel

150 = 40mm (1 1/2")  
200 = 50mm (2")  
300 = 75mm (3")

400 = 110mm (4")  
350 = 75mm (3")  
and higher

#### PT - 322 (Pulse Transmitters)

PT =  
Pulse Transmitter

322 = No read out  
3002 = Digital readout

**Operating Specifications (Sensors)**

- Accuracy: ± 1% (full scale)
- Velocity: 1/2 - 30 feet (0,15 - 9,2 meters) per second, depending on model
- Pressure: 400 psi (27,5 bars) (max) on metal models; 100 psi (6,9 bars) (max) on plastic models
- Temperature: 220° F (105° C) (max) on metal models; 140° F (60° C) (max) on plastic models

**Operating Specifications (Transmitters)**

- Input required:
  - 12-30 VDC/VAC on PT322
  - 10.5-26 VAC (12-24 VAC rec.) on PT 1502
  - 12-24 VAC/VDC on PT 3002
- Output: pulse output
- Operating Temp: -4° F-158° F (-20° C to 70° C)

**Rain Bird Flow Sensor K, Offset and Suggested Operating Range**

The following tables indicate the suggested flow range for Rain Bird Flow Sensors. Rain Bird Sensors will operate both above and below the indicated flow rates. However, good design practice dictates the use of this range for best performance. Sensors should be sized for flow rather than pipe size.

Flow Sensor Models			
Part Number	Model Number	Description	Dimensions
<b>Plastic Tee's</b>			<b>Length x Width x Height</b>
M80118	IFS400PFL	4" (110mm) PVC Tee flow sensor with DIN Flanged ends	340 mm x 220 mm x 240 mm
M80117	IFS300PBSP	3" (75mm) PVC Tee flow sensor with Female BSP straight threaded ends	248 mm x 114 mm x 176 mm
M80116	IFS200PBSP	2" (50mm) PVC Tee flow sensor with Female BSP straight threaded ends	225 mm x 89 mm x 151 mm
M80115	IFS150PBSP	1 1/2" (40mm) PVC Tee flow sensor with Female BSP straight threaded ends	213 mm x 89 mm x 145 mm
M80114	IFS100PBSP	1" (25mm) PVC Tee flow sensor with Female BSP straight threaded ends	172 mm x 63.5 mm x 132 mm *
M80113	IFS075PBSP	¾" (20mm) PVC Tee flow sensor with Female BSP straight threaded ends	172 mm x 63.5 mm x 130 mm *
M80112	IFS050PBSP	½" (12mm) PVC Tee flow sensor with Female BSP straight threaded ends	155 mm x 50.8 mm x 121 mm *
<b>Inserts</b>			<b>Length x Diameter</b>
M80106	FS350SS	Stainless Steel Insert	181 mm x 76 mm
M80105	FS350B	Brass Insert	181 mm x 76 mm
<b>Wind Sensor</b>			<b>Length x Width x Height</b>
M80302	ANEMOMETER	Wind Speed Monitor - Anemometer	56 cm x 20 cm x 20 cm
<b>Pulse Transmitters</b>			<b>Length x Width x Height</b>
M80201	PT322	Pulse Transmitter, no display	93 mm x 56 mm x 44 mm
M80206	PT3002	Pulse Transmitter, LCD display	96 mm x 56 mm x 96 mm
M80202	PT322SW	PT322 Programming Software	-
M80204	PTPWRSUPP	Pulse Transmitter Power Supply	-
M80205	NEMACAB	NEMA Enclosure for PT3002 (only)	-
<b>Accessories</b>			
M80303	FSTINSERT	Flanged Irrigation PPS Insert Assembly	-
M80301	FSSURGEKIT	Flow Sensor Surge Protection Kit	-
M13012	SD211TURF	Sensor Decoder for Decoder Systems	-
M51200	DECPULLR	Pulse Decoder For Two Wire Satellites	-

K Value, Offset and Suggested Operating Range						
Model	Description	K Value	Offset	Suggested Operating Range (Gallons/Minute)	Suggested Operating Range (Liters/Minute)	Suggested Operating Range (Cubic Meters/Hour)
<b>Plastic Tee's</b>						
IFS400PFL	4" (110mm) PVC Tee flow sensor with DIN Flanged ends	13.7424	0.23707	40 - 500	150 - 1890	9.1 - 113.6
IFS300PBSP	3" (75mm) PVC Tee flow sensor with Female BSP straight threaded ends	8.309	0.227	20 - 300	78 - 1134	4.5 - 68.1
IFS200PBSP	2" (50mm) PVC Tee flow sensor with Female BSP straight threaded ends	2.8429	0.1435	10 - 200	36 - 756	2.3 - 45.4
IFS150PBSP	1 1/2" (40mm) PVC Tee flow sensor with Female BSP straight threaded ends	1.697	-0.316	5 - 100	18 - 378	1.1 - 22.7
IFS100PBSP	1" (25mm) PVC Tee flow sensor with Female BSP straight threaded ends	0.26112	1.2	5.4 - 53.9	20.4 - 204	1.2 - 12.2 *
IFS075PBSP	¾" (20mm) PVC Tee flow sensor with Female BSP straight threaded ends	0.1563	0.9	3.3 - 33.2	12.6 - 125.8	0.75 - 7.5 *
IFS050PBSP	½" (12mm) PVC Tee flow sensor with Female BSP straight threaded ends	0.078	0.9	1.9 - 18.9	7.2 - 71.7	0.43 - 4.3 *
<b>Inserts</b>						
FS350B	Brass Insert Flow Sensor	Depends on Pipe Type and Size - See Chart Below				
FS350SS	Stainless Steele Insert Flow Sensor	Depends on Pipe Type and Size - See Chart Below				

\* discontinued models

**FS350B and FS350SS: K Value, Offset and Suggested Operating Range**

Pipe Size	Pipe O.D.	Pipe I.D.	K Value	Offset	Suggested Operating Range (Gallons/Minute)	Suggested Operating Range (Liters/Minute)	Suggested Operating Range (Cubic Meters/Hour)
3 inch Sch 10S	3.500"	3.260"	5.009	0.09	12-400	50-1500	0-90
Std. Wt., Sch 40	3.5"	3.068"	4.362	0.063	12-400	50-1500	0-90
Extra Strong, Sch 80	3.5"	2.900"	3.858	0.043	12-400	50-1500	0-90
PVC Class 125	3.5"	3.284"	5.094	0.093	12-400	50-1500	0-90
PVC Class 160	3.5"	3.230"	4.902	0.085	12-400	50-1500	0-90
PVC Class 200	3.5"	3.166"	4.682	0.076	12-400	50-1500	0-90
4 inch Sch 10S	4.5"	4.260"	9.597	0.241	20-600	80-2300	0-140
Std. Wt., Sch 40	4.5"	4.026"	8.34	0.229	20-600	80-2300	0-140
Extra Strong, Sch 80	4.5"	3.826"	7.354	0.188	20-600	80-2300	0-140
PVC Class 125	4.5"	4.224"	9.396	0.24	20-600	80-2300	0-140
PVC Class 160	4.5"	4.154"	9.013	0.24	20-600	80-2300	0-140
PVC Class 200	4.5"	4.072"	8.578	0.239	20-600	80-2300	0-140
5 inch Sch 10S	5.563"	5.295"	16.305	0.25	30-900	110-3400	10-200
Std. Wt., Sch 40	5.50"	5.047"	14.674	0.248	30-900	110-3400	10-200
Extra Strong, Sch 80	5.50"	4.813"	13.165	0.246	30-900	110-3400	10-200
6 inch Sch 10S	6.625"	6.357"	24.089	0.26	50-1,500	190-5700	10-340
Std. Wt., Sch 40	6.5"	6.065"	21.574	0.257	50-1,500	190-5700	10-340
Extra Strong, Sch 80	6.5"	5.761"	19.457	0.254	50-1,500	190-5700	10-340
PVC Class 125	6.625"	6.217"	22.853	0.258	50-1,500	190-5700	10-340
PVC Class 160	6.625"	6.115"	21.968	0.257	50-1,500	190-5700	10-340
PVC Class 200	6.625"	5.993"	21.068	0.256	50-1,500	190-5700	10-340
8 inch Sch 10S	8.625"	8.329"	43.914	0.286	80-2,500	300-9500	20-570
Sch 20	8.625"	8.125"	41.653	0.283	80-2,500	300-9500	20-570
Sch 30	8.625"	8.071"	41.063	0.283	80-2,500	300-9500	20-570
Std. Wt., Sch 40	8.625"	7.981"	40.086	0.281	80-2,500	300-9500	20-570
Sch 60	8.625"	7.813"	38.288	0.279	80-2,500	300-9500	20-570
Extra Strong, Sch 80	8.625"	7.625"	36.315	0.276	80-2,500	300-9500	20-570
PVC Class 125	8.625"	8.095"	41.324	0.283	80-2,500	300-9500	20-570
PVC Class 160	8.625"	7.961"	39.869	0.281	80-2,500	300-9500	20-570
PVC Class 200	8.625"	7.805"	38.203	0.279	80-2,500	300-9500	20-570
10 inch Sch 10S	10.75"	10.420"	70.195	0.321	125-4,000	470-15100	30-910
Sch 20	10.75"	10.250"	67.668	0.318	125-4,000	470-15100	30-910
Sch 30	10.75"	10.136"	66.069	0.316	125-4,000	470-15100	30-910
Sch 40, Std.Wt.	10.75"	10.020"	64.532	0.314	125-4,000	470-15100	30-910
Extra Strong, Sch 60	10.75"	9.750"	61.016	0.309	125-4,000	470-15100	30-910
Sch 80	10.75"	9.564"	58.644	0.306	125-4,000	470-15100	30-910
PVC Class 125	10.75"	10.088"	65.431	0.315	125-4,000	470-15100	30-910
PVC Class 160	10.75"	9.924"	63.272	0.312	125-4,000	470-15100	30-910
PVC Class 200	10.75"	9.728"	60.733	0.309	125-4,000	470-15100	30-910
12 inch Sch 10S	12.75"	12.390"	104.636	0.367	175-5,000	660-18900	40-1140
Sch 20	12.75"	12.250"	102.553	0.364	175-5,000	660-18900	40-1140
Sch 30	12.75"	12.090"	99.347	0.36	175-5,000	660-18900	40-1140
Std. Wt., Sch 40S	12.75"	12.000"	97.576	0.358	175-5,000	660-18900	40-1140
Sch 40	12.75"	11.938"	96.369	0.356	175-5,000	660-18900	40-1140
Sch 60	12.75"	11.625"	90.441	0.348	175-5,000	660-18900	40-1140
Extra Strong	12.75"	11.750"	92.775	0.351	175-5,000	660-18900	40-1140
Sch 80	12.74"	11.376"	85.922	0.342	175-5,000	660-18900	40-1140
PVC Class 125	12.75"	11.966"	96.912	0.357	175-5,000	660-18900	40-1140
PVC Class 160	12.75"	11.770"	93.152	0.352	175-5,000	660-18900	40-1140
PVC Class 200	12.75"	11.538"	88.842	0.346	175-5,000	660-18900	40-1140
14 inch Sch 10S	14.00"	13.500"	122.307	0.391	200-6,000	760-22700	50-1360
Sch 20	14.00"	13.375"	120.216	0.388	200-6,000	760-22700	50-1360
Std. Wt., Sch 30	14.00"	13.250"	118.151	0.385	200-6,000	760-22700	50-1360
Sch 40	14.00"	13.124"	116.096	0.382	200-6,000	760-22700	50-1360
Sch 60	14.00"	12.814"	111.148	0.376	200-6,000	760-22700	50-1360
Extra Strong	14.00"	13.00"	114.098	0.33	200-6,000	760-22700	50-1360
Sch 80	14.00"	12.50"	106.299	0.369	200-6,000	760-22700	50-1360
16 inch Sch 10S	16.00"	15.500"	159.243	0.44	300-9,000	1140-34100	70-2040

**FS350B and FS350SS: K Value, Offset and Suggested Operating Range**

Pipe Size	Pipe O.D.	Pipe I.D.	K Value	Offset	Suggested Operating Range (Gallons/Minute)	Suggested Operating Range (Liters/Minute)	Suggested Operating Range (Cubic Meters/Hour)
Sch 20	16.00"	15.375"	156.742	0.436	300-9,000	1140-34100	70-2040
Std. Wt., Sch 30	16.00"	15.250"	154.267	0.433	300-9,000	1140-34100	70-2040
Sch 60	16.00"	14.688"	143.456	0.419	300-9,000	1140-34100	70-2040
Extra Strong, Sch 40	16.00"	15.000"	149.394	0.427	300-9,000	1140-34100	70-2040
Sch 80	16.00"	14.314"	136.548	0.41	300-9,000	1140-34100	70-2040
18 inch Sch 10S	18.00"	17.500"	202.739	0.498	350-10,000	1320-37900	80-2270
Sch 20	18.00"	17.375"	199.828	0.494	350-10,000	1320-37900	80-2270
Sch 30	18.00"	17.124"	194.061	0.486	350-10,000	1320-37900	80-2270
Std. Wt.	18.00"	17.250"	196.943	0.49	350-10,000	1320-37900	80-2270
Sch 40	18.00"	16.876"	188.464	0.479	350-10,000	1320-37900	80-2270
Sch 60	18.00"	16.500"	180.171	0.469	350-10,000	1320-37900	80-2270
Extra Strong	18.00"	17.000"	191.25	0.482	350-10,000	1320-37900	80-2270
Sch 80	18.00"	16.126"	172.152	0.457	350-10,000	1320-37900	80-2270
20 inch Std. Wt., Sch 20	20.00"	19.25"	246.179	0.555	400-12,000	1510-45400	90-2730
Sch 40	20.00"	18.812"	234.836	0.54	400-12,000	1510-45400	90-2730
Extra Strong, Sch 30	20.00"	19.000"	239.666	0.547	400-12,000	1510-45400	90-2730
Sch 80	20.00"	17.938"	213.14	0.511	400-12,000	1510-45400	90-2730
22 inch Std. Wt., Sch 20	22.00"	21.25"	301.975	0.621	500-15,000	1890-56800	110-3410
Extra Strong, Sch 30	22.00"	21.00"	294.642	0.616	500-15,000	1890-56800	110-3410
Sch 80	22.00"	19.75"	259.513	0.573	500-15,000	1890-56800	110-3410
24 inch Std. Wt., Sch 20	24.00"	23.25"	364.331	0.666	600-18,000	2270-68100	140-4090
Extra Strong	24.00"	23.00"	356.178	0.66	600-18,000	2270-68100	140-4090
Sch 40	24.00"	22.624"	344.109	0.652	600-18,000	2270-68100	140-4090
Sch 80	24.00"	21.562"	311.271	0.628	600-18,000	2270-68100	140-4090
26 inch Sch 10	26.00"	25.376"	437.809	0.719	700-21,000	2650-79500	160-4770
Std. Wt.	26.00"	25.25"	433.247	0.716	700-21,000	2650-79500	160-4770
Sch 20, Extra Strong	26.00"	25.00"	424.274	0.709	700-21,000	2650-79500	160-4770
28 inch Sch 10	28.00"	27.376"	513.698	0.774	900-23,000	3410-87100	200-5220
Std. Wt.	28.00"	27.25"	508.723	0.77	900-23,000	3410-87100	200-5220
Extra Strong, Sch 20	28.00"	27.00"	498.93	0.763	900-23,000	3410-87100	200-5220
30 inch Sch 10	30.00"	29.376"	596.147	0.833	1,000-30,000	3790-113600	230-6810
Std. Wt.	30.00"	29.25"	590.759	0.829	1,000-30,000	3790-113600	230-6810
Sch 20, Extra Strong	30.00"	29.00"	580.146	0.822	1,000-30,000	3790-113600	230-6810
32 inch Sch 10	32.00"	31.376"	685.156	0.897	1,200-35,000	4540-132500	270-7950
Std. Wt.	32.00"	31.25"	679.355	0.893	1,200-35,000	4540-132500	270-7950
Sch 20, Extra Strong	32.00"	31.00"	667.922	0.885	1,200-35,000	4540-132500	270-7950
Sch 40	32.00"	30.624"	650.919	0.873	1,200-35,000	4540-132500	270-7950
34 inch Sch 10	34.00"	33.312"	777.566	0.964	1,300-40,000	4920-151400	300-9080
Std. Wt.	34.00"	33.25"	774.511	0.962	1,300-40,000	4920-151400	300-9080
Extra Strong, Sch 20	34.00"	33.00"	762.258	0.953	1,300-40,000	4920-151400	300-9080
Sch 40	34.00"	32.624"	744.022	0.94	1,300-40,000	4920-151400	300-9080
36 inch Sch 10	36.00"	35.376"	882.855	1.04	1,500-45,000	5680-170300	340-10220
Std. Wt.	36.00"	35.25"	876.227	1.035	1,500-45,000	5680-170300	340-10220
Sch 20, Extra Strong	36.00"	35.00"	863.154	1.025	1,500-45,000	5680-170300	340-10220
Sch 40	36.00"	34.50"	837.315	1.007	1,500-45,000	5680-170300	340-10220

## Specifications

### Model IFS150PBSP, IFS200PBSP, or IFS300PBSP Flow Sensor

The flow sensor shall be an in-line type with a non-magnetic, spinning impeller (paddle wheel) as the only moving part. The electronics housing shall be glass-filled PPS. The impeller shall be glass-filled nylon or Tefzel with a UHMWPE or Tefzel sleeve bearing. The shaft material shall be tungsten carbide. The electronics housing shall have two, ethylenepropylene O-Rings and shall be easily removed from the meter body. The sensor electronics will be potted in an epoxy compound designed for prolonged immersion. Electrical connections shall be 2 single conductor 18 AWG leads 48 inches (1,2 meters) long. Insulation shall be direct burial "UF" type colored red for the positive lead and black for the negative lead. The sensor shall be capable of operating in line pressure up to 100 psi (6,9 bars) and liquid temperatures up to 140° F (60° C), and operating in flows of 1/2 foot (0,15 meters) per second to 30 feet (9,2 meters) per second with linearity of  $\pm 1\%$  and repeatability of  $\pm 1\%$ . The meter body shall be fabricated from Schedule 80 PVC Tees, available in 40mm (1 1/2"), 50mm (2") and 75mm (3") with Female BSP straight threaded end connections. This flow sensor shall be Rain Bird Model IFS150PBSP, IFS200PBSP, or IFS300PBSP.

### Model IFS400PFL Flow Sensor

The flow sensor shall be an in-line type with a non-magnetic, spinning impeller (paddle wheel) as the only moving part. The electronics housing shall be glass-filled PPS. The impeller shall be glass-filled nylon or Tefzel with a UHMWPE or Tefzel sleeve bearing. The shaft material shall be tungsten carbide. The electronics housing shall have two, ethylenepropylene O-Rings and shall be easily removed from the meter body. The sensor electronics will be potted in an epoxy compound designed for prolonged immersion. Electrical connections shall be 2 single conductor 18 AWG leads 48 inches (1,2 meters) long. Insulation shall be direct burial "UF" type colored red for the positive lead and black for the negative lead. The sensor shall be capable of operating in line pressure up to 100 psi (6,9 bars) and liquid temperatures up to 140° F (60° C), and operating in flows of 1/2 foot (0,15 meters) per second to 30 feet (9,2 meters) per second with linearity of  $\pm 1\%$  and repeatability of  $\pm 1\%$ . The meter body shall be fabricated from Schedule 80 PVC Tees, available in 110mm (4") with DIN Flanged end connections. This flow sensor shall be Rain Bird Model IFS400PFL.

### Model FS350B & FS350SS Flow Sensors

The flow sensor shall be an insertion type with a nonmagnetic, spinning impeller (paddle wheel) as the only moving part. The sensor sleeve will be brass (or 316 stainless steel) with the sensor housing being PPS. The impeller shall be glassfilled nylon or Tefzel with a UHMWPE or Tefzel sleeve. The shaft material shall be tungsten carbide. The sensor will be supplied with a 2" (50mm) NPT adapter for installation into any commercially available weld-on fitting or pipe saddle. The adapter shall have two, ethylenepropylene O-Rings. The sensor electronics will be potted in an epoxy compound designed for prolonged immersion. Electrical connections shall be 2 single conductor 18AWG leads 48 inches (1,2 meters) long. Insulation shall be direct burial "UF" type colored red for the positive lead and black for the negative lead. Insertion of the sensor into any pipe size shall be 1 1/2" (40mm) from the inside wall to the end of the sensor housing. The sensor shall be capable of operating in line pressures up to 400 psi (27,5 bars) and liquid temperatures up to 220° F (105° C), and operating in flows of 1/2 foot (0,15 meters) per second to 30 feet (9,2 meters) per second. This flow sensor shall be Rain Bird Model FS350B (FS350SS).

### Model PT322 Pulse Output Transmitter

The Pulse Output Transmitter shall receive signals for any Rain Bird flow sensor and produce a dry contact closure in units of measure that can be defined by the user. Calibration shall be achieved by connecting to a computer with Rain Bird PT322SW software. All information set in the software is sent to the PT322 via a supplied cable. The PT322 shall feature two diagnostic LED's, one corresponding to the input signal and one corresponding to the output signal. Model PT322 transmitter shall operate on 12-30 VDC/VAC power. Models shall be provided in epoxy filled enclosures. The Pulse Output Transmitter shall be Rain Bird Model PT322.

### Model PT3002 Flow Monitor

The flow monitor shall be a microprocessor based digital unit capable of calculating and displaying both rate of flow and total flow on a two line by sixteen character alpha-numeric LCD. The flow monitor shall accept digital inputs or optional sine wave or analog signal and may be field configured to display rate and total values in any unit of measure. All data shall be entered via five keys mounted on the front panel. The monitor shall feature a software lock to protect the entered data from unauthorized changes. A nonvolatile memory, requiring no battery backup shall protect the data from electronic losses. The Model PT3002 shall conform to DIN standard dimensions for panel mounting, and shall feature a NEMA 4X rated front panel, in an optional NEMA 4 wall mount cabinet. Monitor shall operate on power of 12-24 VAC/VDC. The flow monitor shall feature standard open collector transistor outputs, one based on rate and one based on total. Set points or time delays for rate, scaling or pulse width for total may be configured in the field. Options shall include analog inputs, analog output, or control relays, all programmable from the keypad. The flow monitor shall be Rain Bird Model PT3002.

*Tefzel® is a registered trademark of DuPont.*

#### Rain Bird Corporation

6991 E. Southpoint Road  
Tucson, AZ 85756  
Phone: (520) 741-6100  
Fax: (520) 741-6522

#### Rain Bird Technical Services

(800) RAINBIRD (1-800-724-6247)  
(U.S. and Canada)

#### Rain Bird Corporation

970 West Sierra Madre Avenue  
Azusa, CA 91702  
Phone: (626) 812-3400  
Fax: (626) 812-3411

#### Specification Hotline

800-458-3005 (U.S. and Canada)

#### Rain Bird International, Inc.

1000 West Sierra Madre Ave.  
Azusa, CA 91702  
Phone: (626) 963-9311  
Fax: (626) 852-7343

The Intelligent Use of Water™  
[www.rainbird.com](http://www.rainbird.com)