

GEKA® plus irrigation wands Soft Rain with metal watering head

- Advantage / benefit: **quantity control valve** (ball valve)
with rotatable and replaceable outlet pipe and
watering head for large-scale, soft water spray
- Material: watering head (50.6399.9), outlet pipe and cap nut: aluminium;
soft handle: plastic Thermoflex; threaded insert: brass;
ball valve (50.5548): brass nickel-plated;
ball: hard chrome-plated with O-rings PTFE;
toggle: stainless steel; dirt filter with flat seal ring:
plastic PE, fabric V2A;
GEKA® plus quick coupling: brass
- Colour: handle black; toggle painted in red
- Connection: GEKA® plus quick coupling,
suitable for hose sizes from 3/8" to 1½"
- Options: **large selection of watering heads, showers and nozzles**
on the following pages
outlet pipe either 40 cm, 60 cm, 90 cm or 120 cm long
with cap nut

| Water flow rate at 3 bar l/min | approx. 87 | approx. 87 | approx. 87 | approx. 87 |
|--------------------------------|------------|------------|------------|------------|
| Sieve hole Ø mm | 0.7 | 0.7 | 0.7 | 0.7 |
| Pipe Ø in mm | 19 x 1 | 19 x 1 | 19 x 1 | 19 x 1 |
| Pipe bend | 35° | 35° | 35° | 35° |
| Pipe length in cm | 40 | 60 | 90 | 120 |
| PU units | 1 | 1 | 1 | 1 |
| Covering box units | 20 | 10 | 10 | 10 |
| Item no. | 50.2594.9 | 50.2596.9 | 50.2599.9 | 50.2120.9 |



GEKA® plus watering wands Soft Rain with plastic/metal watering head

- Advantage / benefit: **quantity control valve** (ball valve)
with rotatable and replaceable outlet pipe and
watering head for large-scale, soft water spray
- Material: watering head (50.7399.9): plastic; outlet pipe with cap nut and
watering head plate: aluminium; soft handle: plastic Thermoflex;
ball valve (50.5649): plastic PP COP/POM with O-ring EPDM;
dirt filter with flat seal ring: plastic PE, fabric V2A;
GEKA® plus quick coupling: brass
- Colour: ball valve, handle and watering head black; lever red
- Connection: GEKA® plus quick coupling,
suitable for hose sizes from 3/8" to 1½"
- Options: **large selection of watering heads, showers and nozzles**
on the following pages
outlet pipe either 40 cm, 60 cm, 90 cm or 120 cm long
with cap nut

| Water flow rate at 3 bar l/min | approx. 87 | approx. 87 | approx. 87 | approx. 87 |
|--------------------------------|------------|------------|------------|------------|
| Sieve hole Ø mm | 0.7 | 0.7 | 0.7 | 0.7 |
| Pipe Ø in mm | 19 x 1 | 19 x 1 | 19 x 1 | 19 x 1 |
| Pipe bend | 35° | 35° | 35° | 35° |
| Pipe length in cm | 40 | 60 | 90 | 120 |
| PU units | 1 | 1 | 1 | 1 |
| Item no. | 50.4594.9 | 50.4596.9 | 50.4599.9 | 50.4620.9 |

