

X2™

This online-capable controller offers rapid schedule programming and advanced water-saving features.

Key Benefits

X2 CONTROLLER BENEFITS

- Number of stations: 4, 6, 8, or 14 (fixed models)
- Backlit display provides optimal visibility in any light
- QuickCheck™ provides simple diagnostics of faulty field wiring
- Suspend irrigation up to 99 days during the off-season
- Easy Retrieve® memory backs up the full irrigation schedule
- Cycle and Soak prevents water waste and runoff in areas with elevation changes or tight soils
- Wi-Fi capable controller automatically managed by Hydrowise® software
- 3 flexible programs with 4 start times each and up to 6-hour run times
- Hide Programs option shows 1 program and 1 start time for simplification
- Short-circuit protection detects wiring faults and skips the station without system damage
- Delay Between Stations for slow-closing valves or pump recharge
- Seasonal adjustment for quicker schedule adjustments without changing run times

WAND WI-FI MODULE BENEFITS

- Simple Wi-Fi plug-in enables remote irrigation management with any X2 Controller
- Standard programming allows for three independent programs featuring six start times each and 24-hour maximum run times
- Predictive Watering™ Technology provides precise weather adjustments for maximum water savings
- Bluetooth Wi-Fi setup or WPS push-button connection makes it easy to connect to a wireless network
- WAND Technology provides easy online irrigation management with controller status and faulty wiring alerts
- Rapid Programming™ Technology lets you send preprogrammed schedules to any X2 Controller in seconds, so you get jobs done quicker
- Compatibility with Amazon Alexa™, Control4® and HomeSeer home automation technology enables simple, centralised voice control of the irrigation system

Operating Specifications

- Transformer input: 230 VAC
- Station output (24 VAC): 0.56 A
- Transformer output (24 VAC): 1 A
- P/MV output (24 VAC): 0.28 A

Number of Stations: 4, 6, 8, 14

Type: Fixed

Wi-Fi Capable with WAND



X2

Height: 23 cm
Width: 19 cm
Depth: 10 cm




WAND

Bluetooth and Wi-Fi Module (Optional)

Height: 2 cm
Width: 5 cm
Depth: 5 cm

• Sensor inputs: 1

• Approvals (controller): Plastic
IP44, UL, cUL, FCC, CE, RCM

Model	Approvals (module): Wi-Fi 2.4 GHz b/g/n-Bluetooth 5.0, UI, cUL, FCC, CE, RCM	Warranty period: 2 years (controller and module)	Description
X2-401E			4-station controller, 230 VAC internal transformer with no plug
X2-601E			6-station controller, 230 VAC internal transformer with no plug
X2-801E			8-station controller, 230 VAC internal transformer with no plug
X2-1401E			14-station controller, 230 VAC internal transformer with no plug
X2-401A			4-station controller, 230 VAC internal transformer with Australian plug
X2-601A			6-station controller, 230 VAC internal transformer with Australian plug
X2-801A			8-station controller, 230 VAC internal transformer with Australian plug
X2-1401A			14-station controller, 230 VAC internal transformer with Australian plug

Options Models:

Model	Description
WAND	Bluetooth and Wi-Fi module for Hydrowise water management software
606800	AC solenoid
ROAM-KIT	Remote with up to 1,000 ft. range. Includes transmitter, receiver (SmartPort® wiring harness, and 4 AAA batteries)
ROAMXL-KIT	Remote with up to 2 mile range. Includes transmitter, receiver (SmartPort® wiring harness, and carrying case)