

QUICK COUPLERS

Size: ¾" (20 mm), 1" (25 mm)
Pressure Rating: 10 bar; 1,000 kPa

FEATURES

- 100% interchangeable with major brands*
- Red brass and stainless steel construction
- Heavy-duty thermoplastic locking and non-locking covers
- Optional winged stabilisation and ACME key connection
- Stainless steel lug on 1" (25 mm) and 1¼" (32 mm) keys
- Spring-loaded covers with stainless steel springs for positive closing and protection of valve's sealing components
- Warranty period: 5 years

* HQ compatibility information on page 215



Quick Couplers



Reclaimed Water Option

All locking models have an optional purple TuffTop™ cover for sites using reclaimed water.

HQ PRESSURE LOSS IN BAR					HQ PRESSURE LOSS IN kPa				
Flow m³/hr	HQ-3	HQ-33	HQ-44	HQ-5	Flow l/min	HQ-3	HQ-33	HQ-44	HQ-5
1	0.06	0.07			18.9	5.5	6.9		
2.3	1.12	0.14			37.9	12.4	13.8		
3.4	0.28	0.30	0.15		56.8	28.3	29.6	15.2	
4.5	0.50	0.52	0.30	0.07	75.7	49.6	52.4	30.3	6.9
6.8			0.79	0.21	113.6			79.3	20.7
9.1				0.43	151.4				43.4
11.4				0.63	189.3				63.4
13.6				0.90	227.1				89.6
15.9				1.37	265.0				136.5

QUICK COUPLER, KEY AND HOSE SWIVEL CHARTS							
Model	Inlet Threads	Slots	Body	Colour*	Locking	Key	Swivels
HQ-3RC	¾"	2	1 - Piece	Yellow	No	HK-33	HS-0
HQ-33DRC	¾"	2	2 - Piece	Yellow	No	HK-33	HS-0
HQ-33DLRC	¾"	2	2 - Piece	Yellow	Yes	HK-33	HS-0
HQ-44RC	1" (25 mm) NPT	1	2 - Piece	Yellow	No	HK-44	HS-1 or HS-2
HQ-44LRC	1" (25 mm) NPT	1	2 - Piece	Yellow	Yes	HK-44	HS-1 or HS-2
HQ-44RC-AW	1" (25 mm) NPT	ACME	2 - Piece Wing**	Yellow	No	HK-44A	HS-1 or HS-2
HQ-44LRC-AW	1" (25 mm) NPT	ACME	2 - Piece Wing**	Yellow	Yes	HK-44A	HS-1 or HS-2
HQ-5RC	1" (25 mm) NPT	2	1 - Piece	Yellow	No	HK-55	HS-1 or HS-2
HQ-5LRC	1" (25 mm) NPT	2	1 - Piece	Yellow	Yes	HK-55	HS-1 or HS-2

Notes:

- * All locking cover models are available with purple covers for reclaimed water applications
- ** Anti-rotation stabilisation wings

HQ QUICK COUPLER – SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1 Model	2 Cover Options	3 Additional Options
<p>HQ3 = ¾" Inlet, 1-piece body, 2 slots</p> <p>HQ5 = 1" (25 mm) Inlet, 1-piece body, 2 slots</p> <p>HQ33D = ¾" Inlet, 2-piece body, 2 slots</p> <p>HQ44 = 1" (25 mm) Inlet, 2-piece body, 1 slot or ACME</p>	<p>RC = Yellow rubber cover</p> <p>LRC = Yellow locking rubber cover (Not available for HQ3 body)</p>	<p>(blank) = No option</p> <p>AW = ACME key with anti-rotation wings (Only available for HQ44 body)</p> <p>BSP = BSP threads (Only available for HQ5 body)</p> <p>R = Purple locking cover (reclaimed water ID; only available for LRC models)</p>

Examples:

- HQ3 - RC = HQ3 valve with rubber cover
- HQ44 - LRC = HQ44 valve with locking rubber cover
- HQ44 - LRC - R = HQ44 valve with locking rubber cover and purple locking cover
- HQ44 - LRC - AW - R = HQ valve, with locking rubber cover, ACME key socket, anti-rotation wings and purple locking cover
- HQ5 - LRC - BSP = HQ5 valve with locking rubber cover and BSP threads

HK KEYS

Key Model	Compatible Valve	Compatible Swivel
HK33 = ¾" valve, ¾" key inlet	HQ3, HQ33	HS0
HK44 = 1" (25 mm) valve, 1" (25 mm) key inlet	HQ44	HS1, HS2, HS1B, HS2B
HK44A = 1" (25 mm) valve, ACME key inlet	HQ44AW	HS1, HS2, HS1B, HS2B
HK55 = 1" (25 mm) valve, 1¼" (32 mm) key inlet	HQ5	HS1, HS2, HS1B, HS2B

HS HOSE SWIVELS

Hose Swivel	Compatible Key
HS0 = ¾" inlet, ¾" hose outlet	HK33
HS1 = 1" (25 mm) inlet, ¾" hose outlet	HK44, HK44A, HK55
HS2 = 1" (25 mm) inlet, 1" (25 mm) hose outlet	HK44, HK44A, HK55
HS1B = 1" (25 mm) inlet, ¾" BSP outlet	HK44, HK44A, HK55
HS2B = 1" (25 mm) inlet, 1" (25 mm) BSP outlet	HK44, HK44A, HK55



① HQ5LRC Quick Coupler with HSJ-1 SnapLok™ equipped swing joint

Introducing Hunter's new full line of HSJ heavy-duty swing joints with configurations for every need and every project. There is even a version specifically designed for quick coupler applications. The SnapLok outlet on HSJ-1 models is equipped with accommodations for both rebar and pipe stabilisation, as well as heavy-duty brass outlet threads with a unique anti-rotation locking feature.

See the HSJ swing joints on page 44