

ESP-RZXe WiFi Compatible Fixed Station Controller

ESP-RZXe Series Controllers

The Rain Bird ESP-RZXe WiFi Compatible Series provides a contractor grade, fixed station irrigation controller for residential and light commercial applications.

The ESP-RZXe Controller provides zone based set up that is easier to understand by untrained users. 4, 6 and 8 zone models are available.

Applications

The ESP-RZXe provides flexible scheduling features that make the controller ideal for a wide variety of applications including residential and light-commercial irrigation systems.

Easy to Use

The ESP-RZXe Controller was designed with ease of use in mind. Zone-based scheduling allows every valve to be scheduled independently; no more explaining "programs" to end users, virtually eliminating call-backs. The large LCD display shows all of the programming for each zone at the same time.

Simple graphic based user interface is easy to explain and presents every controller feature at your fingertips.

Easy to Install

The ESP-RZXe Controller requires only two mounting screws. A guide for 1/2" or 3/4" conduit allows for professional installation of field wires into the cabinet.

Controller Hardware

- Plastic wall-mount case
- 2 x AAA batteries for time and date backup
- Wire nuts for outdoor models

Controller Features

- WiFi compatible with the Rain Bird LNK WiFi Module.
- Large LCD display with easy to navigate user interface
- Weather Sensor input with software override
- Master valve/pump start circuit
- Non-Volatile (100- year) program memory
- Programmable under battery power

Scheduling Features

- Zone based scheduling, allows for independent schedules assigned to each zone. (Run times, Start Times and Watering Days are customizable by zone)
- Contractor Rapid Programming™ automatically copies the Start Times and Watering Days from zone 1 to all remaining zones at initial set up
- 6 independent Start Times per zone
- 4 Watering Days options by zone: Custom days of week, ODD calendar days, EVEN calendar days, Cyclic (every 1 – 14 days)
- Manually water ALL zones or SINGLE zone on demand

Advanced Features

- Electronic diagnostic circuit breaker
- Contractor Rapid Programming™ and "Copy previous Zone" for faster initial set up
- Contractor Default™ Save / Restore
- Rain Sensor bypass
- Rain Sensor bypass by Zone
- Manual water SINGLE zone
- Manual water ALL zones

Operating Specifications

- Zone timing: 0 to 199 min
- Seasonal Adjust; -90% to +100%
- Independent schedule per zone
- 6 Start Times per zone
- Program Day Cycles include Custom days of the week, Odd, Even, & Cyclical dates



Indoor Model



Outdoor Model

How To Specify:

ESP-RZXe Indoor Models

RZX4i-230V	Indoor 4 STA ESP-RZXe – 230 V
RZX6i-230V	Indoor 6 STA ESP-RZXe – 230 V
RZX8i-230V	Indoor 8 STA ESP-RZXe – 230 V

ESP-RZXe Outdoor Models

RZX4-230V	Outdoor 4 STA ESP-RZXe – 230 V
RZX6-230V	Outdoor 6 STA ESP-RZXe – 230 V
RZX8-230V	Outdoor 8 STA ESP-RZXe – 230 V

Electrical Specifications

- Input required: 230 VAC \pm 10%, 50Hz
- Output: 24 VAC 650mA
- Power back-up: 2 x AAA batteries maintain time and date while nonvolatile memory maintains the programming

Certifications

- UL, cUL, CE, C-Tick, FCC Part 15, Industry Canada ICES-03, IRAM S-Mark

Dimensions

Indoor Model:

- Width: (16,9 cm)
- Height: (15,0 cm)
- Depth: (3,9 cm)

Outdoor Model:

- Width: (20,1 cm)
- Height: (19,9 cm)
- Depth: (3,9 cm)

Specifications

- The ESP-RZXe Controller shall be of a hybrid type that combines electro-mechanical and microelectronic circuitry capable of fully automatic or manual operation. The controller shall be housed in a wall-mountable, plastic cabinet.
- The controller shall have a fixed zone capacity of 4, 6 or 8 zones depending on the model. All zones shall have the

capability of independently obeying or ignoring the weather sensor. Zone timing shall be from 0 to 199 minutes per start time. The controller shall have a Seasonal Adjustment which adjusts the Run Time for all zones from -90% to +100% in 10% increments.

- The controller shall have independent zone schedules which can have different Start Times, Watering Day cycles, and zone Run Times. Each zone shall have up to 6 Start Times per day that are independent from each other. Available day cycles shall be: By Custom days of the week, Odd, Even and 1-14 days (Cyclic).
 - The controller shall have an LCD display that is capable of displaying each zone's irrigation scheduled Watering Days, Start Times and Run Times in the same screen.
 - The controller shall have an electronic diagnostic circuit breaker that shall sense a zone with an electrical overload or short circuit and shall bypass that zone and continue to operate all other zones.
 - The controller shall have a 365-day calendar backed up against power interruptions by two user replaceable AAA batteries.
 - The controller shall provide the user the ability to bypass the weather sensor for ALL zones or each zone independently.
 - The controller shall offer manual watering of ALL zones sequentially or ONE zone at a time, when manual watering is triggered; the unit shall ignore the status of the weather sensor (if connected) and re-enable the sensor when manual watering is completed.
- The controller shall allow the user to copy the programming from the previous zone to allow for faster and more reliable programming.
 - The controller shall automatically copy the Start Times and Watering Days from zone 1 to all remaining zones of the controller at initial start-up to allow for faster initial set-up of the controller.
 - The controller shall have a mechanism to indicate to the user when AC-Power is not present (if running on batteries).
 - The controller shall provide a method for the installer to save the irrigation schedule into non-volatile memory for easy recall later if unwanted schedule changes are made.
 - The controller shall provide a method for the installer to restore the schedule to the factory fresh condition in order to start programming from a "blank" state.
 - The controller shall provide a method to wire the controller through a 1/2" or 3/4" wire conduit to allow for a more professional installation.
 - The controller shall be manufactured by Rain Bird Corporation in a NAFTA member country.

Rain Bird Europe SNC

BAT A - Parc Clamar
240, rue René Descartes BP 40072
13792 Aix-en-Provence Cedex 3
FRANCE
Tel: (33) 4 42 24 44 61
Fax: (33) 4 42 24 24 72
rbe@rainbird.eu - www.rainbird.eu

Rain Bird France SNC

BAT A - Parc Clamar
240, rue René Descartes BP 40072
13792 Aix-en-Provence Cedex 3
FRANCE
Tel: (33) 4 42 24 44 61
Fax: (33) 4 42 24 24 72
rbf@rainbird.eu - www.rainbird.fr

Rain Bird Deutschland GmbH

Königstraße 10c
70173 Stuttgart
DEUTSCHLAND
Tel: +49 (0) 711 222 54 158
Fax: +49 (0) 711 222 54 200
rbd@rainbird.eu

Rain Bird Ibérica S.A.

C/ Valentín Beato, 22 2ª Izq. fdo
28037 Madrid
ESPAÑA
Tel: (34) 91 632 48 10
Fax: (34) 91 632 46 45
rbib@rainbird.eu - www.rainbird.es
Portugal@rainbird.eu - www.rainbird.pt

Rain Bird Turkey

Çamlık Mh. Dinç Sokak Sk. No.4 D:59-60
34760 Ümraniye, İstanbul
TÜRKİYE
Tel: (90) 216 443 75 23
Fax: (90) 216 461 74 52
rbt@rainbird.eu - www.rainbird.com.tr