

**TORO®****INFINITY® 35/55 SERIES GOLF ROTORS**

The INFINITY 35/55 Series with SMART ACCESS® features a dual trajectory main nozzle that provides exceptional nozzle performance at the 25° standard angle position and great performance in windy applications at the 15° low angle position. And the part/full circle drive and ratcheting riser allows you to adjust the area of coverage to match your seasonal watering needs or meet water rationing mandates in seconds with no additional parts required.

## FEATURES & BENEFITS

### Industry's Largest Nozzle Selection

Nozzles from 25' to 92' radius plus a wide assortment of back nozzles lets you put the precise amount of water exactly where you need it. All nozzles threaded in from front.

### Stainless Steel Valve Seat

Eliminates body damage from rocks and debris. This indestructible stainless steel seat is molded to the body and virtually eliminates body replacements due to seat damage. Standard on all Toro Golf rotors!

### Radius Reduction Screw

Allows for fine tuning the radius to exactly the distance you need. In combination with main nozzle sizing and trajectory adjustment the radius reduction screw can effectively reduce the sprinkler throw down to 30'.

### True Part and Full-Circle in One (40° - 330° part circle)

These sprinklers can be full circle today and part circle tomorrow allowing you to adjust the area of coverage to match your seasonal needs or meet water rationing mandates.



- ✓ Eliminates sprinkler interference
- ✓ Enhances course appearance

142 174 201

WATER SMART 139


### INFINITY® SERIES DISTANCE MARKERS

- Set your course apart with Toro's unique, customizable distance markers
- White (118-6234) and Yellow (118-6235) color options provide excellent visibility
  - Customizable with any graphic image
  - Multiple number and orientation options available
  - Any font style
  - Easy snap-in installation into any INFINITY golf sprinkler

## Smart Access®

Provides top accessibility to all critical components.

- ✓ No digging or unsightly turf repair scars
- ✓ No buried wire splices or ground faults
- ✓ Pilot valve removable with water "ON"
- ✓ Lower long term cost of ownership
- ✓ Customizable marker
- ✓ Replaceable cover if damaged
- ✓ Increased labor efficiency



**Dual Trajectory**  
The 25° setting provides maximum distance of throw and the 15° setting provides improved wind performance, radius reduction and obstacle avoidance.

### INF35 CONVERSION UPGRADES

MODELS	DESCRIPTION
• INF35-3134	INF35 w/31–34 Nozzles (#3 Nozzle Installed)
• INF35-3537	INF35 w/35–37 Nozzles (#5 Nozzle Installed)
• INF35-3134E	INF35 w/31–34 Nozzles (#3 Nozzle Installed), Effluent
• INF35-3537E	INF35 w/35–37 Nozzles (#5 Nozzle Installed), Effluent



### INF55 CONVERSION UPGRADES

MODELS	DESCRIPTION
• INF55-5154	INF55 w/51–54 Nozzles (#3 Nozzle Installed)
• INF55-5558	INF55 w/55–58 Nozzles (#5 Nozzle Installed)
• INF55-59	INF55 w/59 Nozzle
• INF55-5154E	INF55 w/51–54 Nozzles (#3 Nozzle Installed), Effluent
• INF55-5558E	INF55 w/55–58 Nozzles (#5 Nozzle Installed), Effluent
• INF55-59E	INF55 w/59 Nozzle, Effluent



## SPECIFICATIONS

### Operational

- Inlet:
  - INF35: 1" ACME
  - INF55: 1½" ACME
- Radius:
  - INF35: 43' – 83'
  - INF55: 55' – 92'
- Flow Rate:
  - INF35: 8.2 – 47.3 gpm
  - INF55: 14.1 – 61.3 gpm
- Precipitation Rates:
  - INF35: Minimum - .41"/hr; Maximum - .45"/hr
  - INF55: Minimum - .46"/hr; Maximum - .58"/hr
- Pilot Valve: Selectable at 50, 65, 80 and 100 psi
- Recommended Operating Pressure Range: 65-100 psi (maximum – 150 psi and minimum – 40 psi)
- Activation types – Electric Valve-in-Head:
  - Standard Solenoid:
    - 24 VAC, 50/60 Hz
    - Inrush: 0.30 A
    - Holding 0.20 A
  - Spike Guard Solenoid:
    - 24 VAC, 50/60 Hz
    - Inrush: 0.12 A
    - Holding 0.10 A
  - Nickel-Plated Spike Guard Solenoid:
    - 24 VAC, 50/60 Hz
    - Inrush: 0.12 A
    - Holding 0.10 A
  - DC Latching Solenoid (DCLS):
    - Momentary low voltage pulse
  - Integrated Lynx Smart Module w/DCLS:
    - Momentary low voltage pulse

### Additional Features

- INF35 has eight nozzle variations (30, 31, 32, 33, 34, 35, 36 & 37)
- INF55 has nine nozzle variations (51, 52, 53, 54, 55, 56, 57, 58 & 59)
- Three in-line nozzles, rotating stream pattern
- Two back nozzle positions
- Stator variations: 3
- Radius reduction screw 363-4839 for fine tuning
- Ratcheting riser
- Nozzle base clutching

### Dimensions

- SMART ACCESS® Cover and Compartment Diameter:
  - INF35: 7<sup>5</sup>/<sub>8</sub>"
  - INF55: 7<sup>5</sup>/<sub>8</sub>"
- Body height:
  - INF35: 10"
  - INF55: 11<sup>3</sup>/<sub>8</sub>"
- Weight:
  - INF35: 4.26 lbs.
  - INF55: 5.08 lbs.
- Weight – Intergrated with Lynx Smart Module:
  - INF35: 4.95 lbs.
  - INF55: 5.71 lbs.
- Pop-up height to nozzle: 3¼"

### Warranty

- Three years
- Five years when installed with Toro Swing Joints

## Specifying Information—INFINITY 35 & INFINITY 55

INF35-XXX-XX					
Body Inlet	Arc	Nozzle	Pressure Regulation*	Activation Type	Optional
INF3	5	XX	X	X	X
3–1" 5–1½"	5—Part-circle and Full-circle In One	INF35—30, 31, 32, 33, 34, 35, 36, 37 INF55—51, 52, 53, 54, 55, 56, 57, 58, 59	6–65 psi 8–80 psi 1–100 psi	1—Standard Solenoid 2—Spike Guard™ Solenoid 3—Nickel-plated Spike Guard Solenoid 4—DC Latching Solenoid (DCLS) 6—Integrated Lynx Smart Module w/DCLS	7—Effluent

**Example:** When specifying an INF35 Series Sprinkler with #34 nozzle, pressure regulation at 65 psi and Spike Guard you would specify: **INF35-346-2**

































Note: Not all models available.

\* All sprinklers are equipped with the selectable pilot valve that allows settings at 50, 65, 80 and 100 psi.



# INFINITY® 35/55 SERIES GOLF ROTORS

## INFINITY 35 SERIES PERFORMANCE CHART—25°

Front Nozzle Positions	Nozzle Set 30  (White Plug)		Nozzle Set 31  (Yellow)		Nozzle Set 32  (Blue)		Nozzle Set 33  (Brown)		Nozzle Set 34  (Orange)		Nozzle Set 35  (Green)		Nozzle Set 36  (Gray)		Nozzle Set 37  (Black)	
	102-2208		102-6906		102-0726		102-6907		102-0728		102-6955		102-6935		102-6936	
																
	102-5670	102-6942	102-5670	102-5671	102-5670	102-6884	102-5670	102-6884	102-5670	102-6884	102-5670	102-6885	102-6531	102-6885	102-6531	102-6885
Back Nozzle Positions																
	Red Plug		Red Plug		Red Plug		Red Plug		Red Plug		Red Plug		Red Plug		Red Plug	
	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335
psi	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm
50	43	8.2	53	13.8	56	18.3	61	21.7	65	25.3	—	—	—	—	—	—
65	45	10.0	53	15.5	59	20.5	64	24.4	68	28.2	72	34.1	—	—	—	—
80	46	11.5	57	17.3	62	22.7	67	27.1	71	31.1	75	37.8	78	40.3	80	44.0
100	47	13.4	59	19.1	65	24.9	70	29.8	74	34.1	79	40.9	81	43.8	83	47.3

## INFINITY 35 SERIES PERFORMANCE CHART—15°

psi	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm
50	43	8.2	52	13.6	58	18.1	61	21.5	62	25.6	—	—	—	—	—	—
65	45	10.0	54	15.3	60	20.3	64	24.2	65	27.3	69	33.1	—	—	—	—
80	46	11.5	58	17.2	64	22.6	69	26.8	69	30.2	75	36.8	76	39.7	76	42.9
100	47	13.4	60	19.0	66	24.7	71	29.5	72	32.9	78	39.5	82	42.6	82	46.1
Stator	102-6929 Blue				102-1939 Yellow				102-1940 White							
Conversions					INF35-3134								INF35-3537			

■ Not recommended at these pressures. Radius shown in feet.  
 Toro recommends the use of a 1¼" swing joint at flows over 25-Gpm (95-LPM). Sprinkler radius data collected in Toro's zero wind test facility per ASAE standard S398.1.  
 Actual site conditions must be considered when selecting the appropriate nozzle.  
 All sprinklers are equipped with the selectable pilot valve that allows settings at 50, 65, 80 and 100 psi.

## INFINITY 35 NOZZLE APEX

Pressure	Nozzle	Apex at 15°	Apex at 25°
65 psi	31	6' @ 51'	13' @ 54'
	32	6' @ 51'	11' @ 64'
	33	7' @ 59'	13' @ 68'
	34	8' @ 63'	15' @ 74'
	35	9' @ 66'	15' @ 76'
80 psi	36	8' @ 75'	18' @ 83'
	37	9' @ 74'	19' @ 82'

# INFINITY® 35/55 SERIES GOLF ROTORS



## INFINITY 55 SERIES PERFORMANCE CHART—25°

Front Nozzle Positions	Nozzle Set 51		Nozzle Set 52		Nozzle Set 53		Nozzle Set 54		Nozzle Set 55		Nozzle Set 56		Nozzle Set 57		Nozzle Set 58		Nozzle Set 59	
	(Yellow)		(Blue)		(Brown)		(Orange)		(Green)		(Gray)		(Black)		(Red)		(Beige)	
	102-6906		102-0726		102-6907		102-0728		102-6955		102-6935		102-6936		102-6909		102-4259	
	Yellow	Brown	Yellow	Yellow	Yellow	Yellow	Yellow	Yellow	Yellow	Green	Green	Green	Green	Green	Green	Green	Green	Green
	102-5670	102-5671	102-5670	102-6884	102-5670	102-6884	102-5670	102-6884	102-5670	102-6885	102-6531	102-6885	102-6531	102-6885	102-6531	102-6885	102-6531	102-6885
Back Nozzle Positions																		
	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug	Red Plug
	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335	102-4335
psi	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm
50	55	14.1	57	18.5	62	22.3	66	25.8	—	—	—	—	—	—	—	—	—	—
65	57	15.8	60	20.9	65	25.1	69	28.7	73	35.9	—	—	—	—	—	—	—	—
80	59	17.5	61	23.1	68	27.8	72	31.7	76	39.7	80	43.1	83	48.2	85	50.0	89	57.5
100	61	19.3	63	25.3	71	30.3	75	34.5	80	43.5	83	49.0	88	51.5	90	53.9	92	61.3

## INFINITY 55 SERIES PERFORMANCE CHART—15°

psi	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm	Radius	gpm
50	55	14.0	59	16.5	62	22.2	63	25.6	—	—	—	—	—	—	—	—	—	—
65	56	15.6	62	20.7	65	25.0	66	28.5	75	35.3	—	—	—	—	—	—	—	—
80	59	17.4	66	23.0	69	27.7	70	31.5	78	39.0	78	42.4	79	46.9	79	49.5	82	57.2
100	60	19.2	68	25.1	71	30.2	72	34.3	80	41.9	81	47.2	83	52.1	83	53.4	85	60.8
Stator	102-1939 Yellow						102-1940 White						102-1941 White					
Conversions	INF35-3134						INF35-3537						INF55-59					

Not recommended at these pressures. Radius shown in feet.  
 Toro recommends the use of a 1¼" swing joint at flows over 25-gpm (95-LPM). Sprinkler radius data collected in Toro's zero wind test facility per ASAE standard S398.1.  
 Actual site conditions must be considered when selecting the appropriate nozzle.  
 All sprinklers are equipped with the selectable pilot valve that allows settings at 50, 65, 80 and 100 psi.

## INFINITY 55 NOZZLE APEX

Pressure	Nozzle	Apex at 15°	Apex at 25°
65 psi	51	6' @ 51'	13' @ 54'
	52	6' @ 51'	11' @ 64'
	53	7' @ 59'	13' @ 68'
	54	8' @ 63'	15' @ 74'
	55	9' @ 66'	15' @ 76'
80 psi	56	8' @ 75'	18' @ 83'
	57	9' @ 74'	19' @ 82'
	58	10' @ 82'	18' @ 87'
	59	11' @ 81'	21' @ 91'