

TEMPUS® AIR PS

Pressure Sensor Module



The module detects the pressure of your irrigation system.

Thanks to the pre-wired pressure sensor, Tempus® Air PS allows you to check the operating status of your system, to prevent malfunctions and to warn you if pre-set thresholds are exceeded.

The module communicates with the Gateway (3G or Wi-Fi), forwarding the detected data and also allows direct connection from smartphone/tablet via Bluetooth®.

LoRa™ controlled, IP68, battery-powered pressure sensor module.

SPECIFICATIONS AND FEATURES

- LoRa™ radio connection [868-868.6] MHz, 25mW
- 1 input for pressure sensor
- LoRa™ range up to 800m
- Pressure sensor included and pre-wired
- 0-5V analogue input
- Pressure measurement 0-16 bar
- Bluetooth® Smart 4.0 Low Energy
- Warning feature when thresholds exceeded
- Waterproof connector (MetriPack-150)
- Sensor thread: G1/4 EN 837
- Remote management via MyToroTempus App and MyToroTempus.com Web platform
- IP68 waterproof
- Powered by 9V DC battery
- Operating temperature: -20° C/60° C

**NO WIRING.
THE MODULE IS
BATTERY-POWERED**

Discover MyToroTempus App to monitor and control TEMPUS® AIR SYSTEM



Free download on App Store or Google Play



Coding

Code	Description
TEMP-AIR-PS	Tempus® Air PS - Pressure Sensor Module



The pressure sensor is connected to the module directly at the factory

The sensor can be disconnected thanks to its waterproof Metripack-150 connector

Pressure sensor



Metripack-150 waterproof connector included

MANUAL



Battery not included