
Threaded Adaptor 32 × 3/4"







Technical Drawing Dimensions

Product Code	d [mm]	H [mm]	R [mm]	E [mm]	l2 [mm]	Unit Per Bag	Unit Per Carton	Weight [g]
7250327	32	86	3/4"	64	18	1	180	65

Product Specifications

Product Features

Product Code	7250327	Product Components	1 Nut
Product Name	Threaded Adaptor 32 × 3/4"	Nut Material	Polypropylene, high-grade copolymer.
Nominal Diameter Mains [mm]	32	Note	We strongly recommend the use of PTEE tape in threaded connections.
Threaded Outlet Diameter [mm]	3/4"	Unit Per Bag	1
Weight [g]	65	Unit Per Carton	180
Body Material	Polypropylene, high-grade copolymer.	Pressure Rating Water	PN 16

Product Specifications

Product Features

Standards

ISO 17885 for Water Applications, AS/NZS 4129, ISO 7/1, BS 21, DIN 2999, UNI 9561, NEN 3258, AS 1722, DIN 8076

Comments

Male threads are tapered, female threads are parallel.

Chemical Resistance

Polyacetal split rings and NBR o-rings, suitable for water, are supplied as standa rd. CPVC split rings and EPDM or FPM o-rings and seals are available. For aggressive chemical applications, the end user is advised to test suitability.

Operating Temperatures

Maximum temperature of use for fittings and valves is the same as that for polyet hylene pipe and they are not intended for use in hot water applications. They will withstand sub-zero temperatures.