

Customer	Date	1/6/2021
Contact	Project	
Phone number	Project no.	
Email		

5SV14F022T

1016LC911

Operating data

Pump type	Single head pump	Fluid	Water
No. of pumps / Reserve	1 / 0	Operating temperature t A	°C 4
Nominal flow	m ³ /h 0	pH-value at t A	7
Nominal head	m 0	Density at t A	kg/m ³ 1000
Static head	m 0	Kin. viscosity at t A	mm ² /s 1.569
Inlet pressure	kPa 0	Vapor pressure at t A	kPa 100
Environmental temperature	°C 20	Solids	0
Available system NPSH	m 0	Altitude	m 0

Pump data

Make	Lowara	Nominal	m ³ /h ()
Speed	rpm 2900	Flow Max-	m ³ /h 8.5
Number of stages	14	Min-	m ³ /h
Max. casing pressure	kPa	Nominal	m
Max. working pressure	kPa 1036.9	Head at Qmax	m 45.7
Head H(Q=0)	m 110	at Qmin	m 105.7
Weight	kg 33	Shaft power	kW ()
	Max. mm 76	Max. shaft power	kW 1.9
Impeller R designed	mm 76	Efficiency	%
	Min. mm 76	NPSH 3%	m

Pump Materials

Pump body	Stainless steel / AISI 304
Impeller	Stainless steel / AISI 304
Diffuser	Stainless steel / AISI 304
Outer sleeve	Stainless steel / AISI 304
Shaft	Stainless steel / AISI 304
Adapter	Cast iron
Base	Aluminium
Coupling	Aluminium
SEAL HOUSING	Stainless steel / AISI 304
Coupling protection	Stainless steel / AISI 304
Shaft sleeve and bushing	Tungsten carbide
Fill / drain plugs	Stainless steel / AISI 304
Tie rods	Galvanized steel
Wear Ring	Technopolymer PPS

Shaft Seal

e-SV Mechanical seal	Roten
e-SV - Uniten (-30 / +120 °C)	
1 - Rotating part	Silicon Carbide
2 - Stationary part	Resin impregnated carbon
3 - Elastomers	EPDM
4 - Springs	AISI 316
5 - Other components	AISI 316

Motor data

Manufacturer	Lowara	Electric voltage	220 V	Speed	2900 rpm	Insulation class	155 (F)
Specific design	IE3 Three phase surface motor (e-SV)	Frame size	90	Colour			RAL 5010
Type	PLM90B14/322 E3 (220-240/380-415V)						
Rated power	2.2 kW	Degree of protection	IP55				
Electric current	7.97 A						

Remarks:


Customer	Date	1/6/2021
Contact	Project	
Phone number	Project no.	
Email		

5SV14F022T 1016LC911

Hydraulic data

Operating Data Specification		Hydraulic data (duty point)		Impeller design	
Flow	0 m ³ /h	Flow		Impeller R	76 mm
Head	0 m	Head		Frequency	50 Hz
Static head	0 m	MEI >=0,7		Speed	2900 rpm

Power data referred to:
Water [100%] ; 4°C; 1000kg/m³; 1.57mm²/s
 Performance according to ISO 9906:2012 – Grade 3B




Customer	Date	1/6/2021
Contact	Project	
Phone number	Project no.	
Email		

5SV14F022T

1016LC911

Drawing



Dimensions mm

D1	174						Weight	
D2	140						33.2	kg
L1	588							
L2	298							
L3	588							
L4	417							
L5	563							
L6	563							
M	134							