

6GS40T-L4C

Company Contact Phone number Email			Customer Contact Phone number Email			Date Item no. Project Project no.			1/7/2021
Operating data									
1	Pumpe type	Single head pump			Fluid			Water, pure	
2	No. of pumps / Reserve	1 /			Operating temperature t A			°C 4	
3	Nominal flow	m ³ /h	0			pH-v value at t A			7
4	Nominal head	m	0			Density at t A			kg/m ³ 1000
5	Static head	m	0			Kin. viscosity at t A			mm ² /s 1.569
6	Inlet pressure	kPa	0			Vapor pressure at t A			kPa 100
7	Environmental temperature	°C	20			Solids			0
8	Available system NPSH	m	0			Altitude			m 0
Pump data									
9	Pump designation	6GS40T-L4C			Impeller Ø			Max.	mm
10	Design	Borehole pumps						designed	mm
11	Make	Lowara			Flow			Min.	mm
12	Speed	rpm	2900					Nominal	m ³ /h ()
13	Number of stages	38			Head			Max-	m ³ /h 8.4
14	Suction nozzle	/ /						Min-	m ³ /h 2.8
15	Discharge nozzle	/ /			Shaft power			Nominal	m
16	Max. casing pressure	kPa						at Qmax	m 82.5
17	Max. working pressure	kPa	2384.1			at Qmin	m 216.3		
18	Impeller type				Max. shaft power			kW ()	
19	Impeller design				Efficiency			%	
20	Head H(Q=0)	m	240			NPSH 3%			m
21	Weight	kg	38						
Materials									
22	Pump								
23	Valve cap	Stainless steel / AISI 304			Motor adapter			Stainless steel / CF-8 ASTM A743	
24	Valve gasket	NBR			Discharge head			Stainless steel / CF-8 ASTM A743	
25	Valve flange	Stainless steel / AISI 304			Screws, nuts, washers			Stainless steel / AISI 316	
26	Valve locking ring	Stainless steel / AISI 302			BUSH			Technopolymer PU	
27	Adapter ring	Technopolymer PPO			Diffuser			Technopolymer PPO	
28	Upper bush bracket	Technopolymer PPO			Impeller			Technopolymer PPO	
29	Thrust bearing	Stainless steel / AISI 304			Bowl			Stainless steel / AISI 304	
30	WASHER	Stainless steel / AISI 304			Intermediate bush			Stainless steel / CF-8 ASTM A743	
31	Intermediate bush	Technopolymer PPO			Cable guard			Stainless steel / AISI 304	
32	bracket_pos9 Shaft Sleeve	Stainless steel / AISI 304			Shim			Stainless steel / AISI 304	
33	Sleeve	Stainless steel / AISI 304			Upper pump shaft			Stainless steel / AISI 304	
34	Upper sleeve	Stainless steel / AISI 304			Intermediate coupling			Stainless steel / AISI 316	
35	Pump shaft	Stainless steel / AISI 304			Spacer			Stainless steel / AISI 304	
37	Coupling	Stainless steel / AISI 304							
36	Strainer	Stainless steel / AISI 304							
38									
Motor data					Cable				
39	Manufacturer	Lowara	Electric voltage	220 V	Cable type				
40	Specific design	3 phase submersible canned motor (e-GS)			Cable cross section			mm ²	
41	Type	L4C40T235	Electric current	16.4 A	Environmental temperature			°C 20	
42	Rated power	4 kW	Degree of protection	IP68	Cable length			0	
43	Speed	2840 rpm	Insulation class	155 (F)					
44	Frame size	56							
45	Weight	0 kg							
Base plate					Remarks:				
46	Name								
47	Weight	kg							


6GS40T-L4C

Company Contact Phone number Email	Customer Contact Phone number Email	Date Item no. Project Project no.
1/7/2021		
Operating Data Specification	Hydraulic data (duty point)	Impeller design
Flow Head Static head	Flow Head MEI >=0,4	Impeller R Frequency Speed
0 m³/h 0 m 0 m		0 mm 50 Hz 2900 rpm

Power datas referred to:

Water, pure [100%] ; 4°C; 1000kg/m³; 1.57mm²/s

Performance according to ISO 9906:2012 – Grade 3B



6GS40T-L4C

Company Contact Phone number Email	Customer Contact Phone number Email	Date Item no. Project Project no.	1/7/2021
---------------------------------------------	----------------------------------------------	--------------------------------------------	----------

Dimensions

mm

DNM L	Rp 1 ¼ 1974					Suction side / PN
						Discharge side / PN
						Weight 38.4 kg

