

Customer	Date	1/6/2021
Contact	Project	
Phone number	Project no.	
Email		

5HM05P09M5HVBE

104600780

Operating data

Pump type	Single head pump	Fluid	Water
No. of pumps / Reserve	1 / 0	Operating temperature t A	°C 4
Nominal flow	m ³ /h 0	pH-value at t A	7
Nominal head	m 0	Density at t A	kg/m ³ 1000
Static head	m 0	Kin. viscosity at t A	mm ² /s 1.569
Inlet pressure	kPa 0	Vapor pressure at t A	kPa 100
Environmental temperature	°C 20	Solids	0
Available system NPSH	m 0	Altitude	m 0

Pump data

Make	Lowara	Nominal	m ³ /h ()
Speed	rpm 2900	Flow Max-	m ³ /h 7.2
Number of stages	5	Min-	m ³ /h
Max. casing pressure	kPa	Nominal	m
Max. working pressure	kPa 582.8	Head at Qmax	m 16
Head H(Q=0)	m 59	at Qmin	m 59.4
Weight	kg 11	Shaft power	kW ()
Max.	mm 73	Max. shaft power	kW .9
Impeller R designed	mm 73	Efficiency	%
Min.	mm 73	NPSH 3%	m

Pump Materials

Pump body	Stainless steel / AISI 304
Impeller	Technopolymer Noryl
Diffuser	Stainless steel / AISI 304
Shaft	Stainless steel / AISI 304
Adapter	Aluminium
SEAL HOUSING	Stainless steel / AISI 304
Fill / drain plugs	Nickel-plated brass
Wear Ring	Technopolymer
Bolts and screws	Stainless steel / AISI 304

Shaft Seal

e-HM Mechanical seal	Roten
e-HM - Roten	
1 - Rotating part	Aluminium oxide (Ceramic)
2 - Stationary part	Carbon, resin-impregnated
3 - Elastomers	EPDM
4 - Springs	AISI 316
5 - Other components	AISI 316

Motor data

Manufacturer	Lowara	Electric voltage	230 V	Speed	2740 rpm	Insulation class	155 (F)
Specific design	Single phase surface motor			Frame size	71	Colour	RAL 5010
Type	SM71HM../1095 [5H] = 220-240V						
Rated power	0.95 kW	Degree of protection	IP55				
Electric current	6.25 A						

Remarks:

Customer	Date	1/6/2021
Contact	Project	
Phone number	Project no.	
Email		


5HM05P09M5HVBE

104600780

Hydraulic data

Operating Data Specification		Hydraulic data (duty point)		Impeller design	
Flow	0 m ³ /h	Flow		Impeller R	73 mm
Head	0 m	Head		Frequency	50 Hz
Static head	0 m			Speed	2900 rpm

Power data referred to:
Water [100%] ; 4°C; 1000kg/m³; 1.57mm²/s
 Performance according to ISO 9906:2012 – Grade 3B




Customer	Date	1/6/2021
Contact	Project	
Phone number	Project no.	
Email		

5HM05P09M5HVBE

104600780

Drawing



Di mm

A	129					Weight	
D	140					11	kg
Drawing	X						
H	220						
L	392						
PN	10						